



JR Simplot Food Group - 846 Inventory Inquiry/Advice

X12/V4010/846: 846 Inventory Inquiry/Advice

Version: 1.0

Company:

JR Simplot Company

Publication:

8/28/2018

Notes:

edi@simplot.com

Table of Contents

846 Inventory Inquiry/Advice	1
ISA Interchange Control Header	3
GS Functional Group Header	5
ST Transaction Set Header	7
BIA Beginning Segment for Inventory Inquiry/Advice	8
N1 Name	9
N1 Name	10
N3 Address Information	11
N4 Geographic Location	12
LIN Item Identification	13
QTY Quantity	14
CTT Transaction Totals	15
SE Transaction Set Trailer	16
GE Functional Group Trailer	17
IEA Interchange Control Trailer	18

846 Inventory Inquiry/Advice

Functional Group=IB

Purpose: This Draft Standard for Trial Use contains the format and establishes the data contents of the Inventory Inquiry/Advice Transaction Set (846) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used in the following ways: (1) for a seller of goods and services to provide inventory information to a prospective purchaser, with no obligation to the purchaser to acquire these goods or services; (2) for a representative of a seller of goods and services to supply inventory information to that seller; (3) for one location to supply another location with inventory information; and (4) for an inquiry as to the availability of inventory with no obligation on the seller of goods and services to reserve that inventory.

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Reg</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Reg</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BIA	Beginning Segment for Inventory Inquiry/Advice	M	1			Must use

<u>LOOP ID - N1</u>					<u>5</u>	
080	N1	Name	O	1		Used
080	N1	Name	O	1		Used
100	N3	Address Information	O	2		Used
110	N4	Geographic Location	O	1		Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Reg</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<u>LOOP ID - LIN</u>					<u>10000</u>		
010	LIN	Item Identification	M	1		Must use	
<u>LOOP ID - QTY</u>					<u>1</u>		
320	QTY	Quantity	M	1		Used	

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Reg</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	CTT	Transaction Totals	O	1		N3/010	Used
020	SE	Transaction Set Trailer	M	1			Must use

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Reg</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

Notes:

3/010 Number of line items (CTT01) is the accumulation of number of LIN segments. If used, hash total (CTT02) is the sum of the values of the quantities (QTY02) of each QTY segment.

Transaction Example:

```
ST*846*0031~
BIA*00*DD*JR Simplot Co.*20180601~
DTM*090*20180601~
N1*DS*Distributor*9*0000079001234~
N1*WH*Warehouse Name*9*0000009123456~
N3*Street Address~
N4*City*ST*12345~
LIN**MG*000002~
QTY*17*000228.000*LB~
QTY*20*0000000000*LB~
```

LIN**MG*000046~
QTY*17*000040.000*GA~
QTY*20*0000000000*GA~
LIN**MG*000023~
QTY*17*000133.920*LB~
QTY*20*0000000000*LB~
LIN**MG*000027~
QTY*17*000030.500*GA~
QTY*20*0000000000*GA~
LIN**MG*000021~
QTY*17*000243.000*QT~
QTY*20*0000000000*QT~
CTT*5~
SE*24*0031~

ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Must use

Purpose: To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier	M	ID	2/2	Must use
<p>Description: Code to identify the type of information in the Authorization Information</p> <p>CodeList Summary (Total Codes: 7, Included: 1)</p> <p>Code Name</p> <p>00 No Authorization Information Present (No Meaningful Information in I02)</p>						
ISA02	I02	Authorization Information	M	AN	10/10	Must use
<p>Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)</p>						
ISA03	I03	Security Information Qualifier	M	ID	2/2	Must use
<p>Description: Code to identify the type of information in the Security Information</p> <p>CodeList Summary (Total Codes: 2, Included: 1)</p> <p>Code Name</p> <p>00 No Security Information Present (No Meaningful Information in I04)</p>						
ISA04	I04	Security Information	M	AN	10/10	Must use
<p>Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)</p>						
ISA05	I05	Interchange ID Qualifier	M	ID	2/2	Must use
<p>Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified</p>						
ISA06	I06	Interchange Sender ID	M	AN	15/15	Must use
<p>Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element</p>						
ISA07	I05	Interchange ID Qualifier	M	ID	2/2	Must use
<p>Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified</p>						
ISA08	I07	Interchange Receiver ID	M	AN	15/15	Must use
<p>Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to</p>						

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		route data to them				
ISA09	I08	Interchange Date	M	DT	6/6	Must use
		Description: Date of the interchange				
ISA10	I09	Interchange Time	M	TM	4/4	Must use
		Description: Time of the interchange				
ISA11	I10	Interchange Control Standards Identifier	M	ID	1/1	Must use
		Description: Code to identify the agency responsible for the control standard used by the message that is enclosed by the interchange header and trailer				
		All valid standard codes are used. (Total Codes: 1)				
ISA12	I11	Interchange Control Version Number	M	ID	5/5	Must use
		Description: Code specifying the version number of the interchange control segments				
		CodeList Summary (Total Codes: 14, Included: 1)				
		Code Name				
		00401 Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1997				
ISA13	I12	Interchange Control Number	M	NO	9/9	Must use
		Description: A control number assigned by the interchange sender				
ISA14	I13	Acknowledgment Requested	M	ID	1/1	Must use
		Description: Code sent by the sender to request an interchange acknowledgment (TA1)				
		All valid standard codes are used. (Total Codes: 2)				
ISA15	I14	Usage Indicator	M	ID	1/1	Must use
		Description: Code to indicate whether data enclosed by this interchange envelope is test, production or information				
		CodeList Summary (Total Codes: 3, Included: 2)				
		Code Name				
		P Production Data				
		T Test Data				
ISA16	I15	Component Element Separator	M		1/1	Must use
		Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator				

GS Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

Purpose: To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code	M	ID	2/2	Must use
<p>Description: Code identifying a group of application related transaction sets</p> <p>CodeList Summary (Total Codes: 240, Included: 1)</p> <p>Code Name</p> <p>IB Inventory Inquiry/Advice (846)</p>						
GS02	142	Application Sender's Code	M	AN	2/15	Must use
<p>Description: Code identifying party sending transmission; codes agreed to by trading partners</p>						
GS03	124	Application Receiver's Code	M	AN	2/15	Must use
<p>Description: Code identifying party receiving transmission; codes agreed to by trading partners</p>						
GS04	373	Date	M	DT	8/8	Must use
<p>Description: Date expressed as CCYYMMDD</p>						
GS05	337	Time	M	TM	4/8	Must use
<p>Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)</p>						
GS06	28	Group Control Number	M	N0	1/9	Must use
<p>Description: Assigned number originated and maintained by the sender</p>						
GS07	455	Responsible Agency Code	M	ID	1/2	Must use
<p>Description: Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480</p> <p>CodeList Summary (Total Codes: 2, Included: 1)</p> <p>Code Name</p> <p>X Accredited Standards Committee X12</p>						
GS08	480	Version / Release / Industry Identifier Code	M	AN	1/12	Must use
<p>Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code</p>						

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		in DE455 in GS segment is T, then other formats are allowed				
		CodeList Summary (Total Codes: 39, Included: 1)				
		<u>Code</u>		<u>Name</u>		
		004010		Draft Standards Approved for Publication by ASC X12 Procedures Review Board through October 1997		

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use
		Description: Code uniquely identifying a Transaction Set				
		CodeList Summary (Total Codes: 298, Included: 1)				
		Code Name				
		846 Inventory Inquiry/Advice				
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

BIA Beginning Segment for Inventory Inquiry/Advice

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

Purpose: To indicate the beginning of an Inventory Inquiry/Advice Transaction Set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BIA01	353	Transaction Set Purpose Code	M	ID	2/2	Must use
		Description: Code identifying purpose of transaction set				
		CodeList Summary (Total Codes: 65, Included: 1)				
		Code Name				
		00 Original				
BIA02	755	Report Type Code	M	ID	2/2	Must use
		Description: Code indicating the title or contents of a document, report or supporting item				
		CodeList Summary (Total Codes: 522, Included: 1)				
		Code Name				
		DD Distributor Inventory Report				
BIA03	127	Reference Identification	M	AN	1/30	Must use
		Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier				
BIA04	373	Date	M	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD				
		User Note 1: <i>Date inventory taken.</i>				

N1 Name

Pos: 080	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used**Purpose:** To identify a party by type of organization, name, and code**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use
Description: Code identifying an organizational entity, a physical location, property or an individual						
CodeList Summary (Total Codes: 1312, Included: 1)						
Code Name						
DS Distributor						
N102	93	Name	X	AN	1/60	Used
Description: Free-form name						
User Note 1: <i>Simplot</i>						
N103	66	Identification Code Qualifier	X	ID	1/2	Used
Description: Code designating the system/method of code structure used for Identification Code (67)						
CodeList Summary (Total Codes: 215, Included: 1)						
Code Name						
9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix						
N104	67	Identification Code	X	AN	2/80	Used
Description: Code identifying a party or other code						
User Note 1: <i>J. R. Simplot Co.DUNS+4 0377918920000</i>						

N1 Name

Pos: 080	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used**Purpose:** To identify a party by type of organization, name, and code**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use
Description: Code identifying an organizational entity, a physical location, property or an individual						
CodeList Summary (Total Codes: 1312, Included: 1)						
Code Name						
WH Warehouse						
N102	93	Name	X	AN	1/60	Used
Description: Free-form name						
User Note 1: <i>Warehouse Name</i>						
N103	66	Identification Code Qualifier	X	ID	1/2	Used
Description: Code designating the system/method of code structure used for Identification Code (67)						
CodeList Summary (Total Codes: 215, Included: 1)						
Code Name						
9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix						
N104	67	Identification Code	X	AN	2/80	Used
Description: Code identifying a party or other code						
User Note 1: <i>J.R. Simplot Co. Branch Plant Number</i>						

N3 Address Information

Pos: 100	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

Purpose: To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

N4 Geographic Location

Pos: 110	Max: 1
Heading - Optional	
Loop: N1	Elements: 3

User Option (Usage): Used

Purpose: To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	O	AN	2/30	Used
		Description: Free-form text for city name				
N402	156	State or Province Code	O	ID	2/2	Used
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	O	ID	3/15	Used
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				

Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

LIN Item Identification

Pos: 010	Max: 1
Detail - Mandatory	
Loop: LIN	Elements: 2

User Option (Usage): Must use

Purpose: To specify basic item identification data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LIN02	235	Product/Service ID Qualifier	M	ID	2/2	Must use
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 477, Included: 1)				
		Code Name				
		MG Manufacturer's Part Number				
LIN03	234	Product/Service ID	M	AN	1/48	Must use
		Description: Identifying number for a product or service				

QTY Quantity

Pos: 320	Max: 1
Detail - Mandatory	
Loop: QTY	Elements: 3

User Option (Usage): Used

Purpose: To specify quantity information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
QTY01	673	Quantity Qualifier	M	ID	2/2	Must use
Description: Code specifying the type of quantity						
CodeList Summary (Total Codes: 832, Included: 2)						
Code Name						
17 Quantity on Hand, total amount of product physically on the floor.						
20 Unusable Quantity						
QTY02	380	Quantity	X	R	1/15	Used
Description: Numeric value of quantity						
QTY03	C001	Composite Unit of Measure	O	Comp		Used
Description: To identify a composite unit of measure(See Figures Appendix for examples of use)						
QTY03-01	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
CodeList Summary (Total Codes: 794, Included: 2)						
Code Name						
CA Case						
LB Pound						

CTT Transaction Totals

Pos: 010	Max: 1
Summary - Optional	
Loop: N/A	Elements: 1

User Option (Usage): Used

Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	NO	1/6	Must use

Description: Total number of line items in the transaction set

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

SE Transaction Set Trailer

Pos: 020	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
		Description: Total number of segments included in a transaction set including ST and SE segments				
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use
		Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element				
GE02	28	Group Control Number	M	N0	1/9	Must use
		Description: Assigned number originated and maintained by the sender				

IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	N0	1/5	Must use
		Description: A count of the number of functional groups included in an interchange				
IEA02	I12	Interchange Control Number	M	N0	9/9	Must use
		Description: A control number assigned by the interchange sender				