

O L E A N T

LYNASUSPENSUS



Materials: Brass Extrusion, Polycarbonate diffuser
Designed by: Peter Danczkay
24 VDC 50,000 h L90/F50¹

Standard Sizes:
1010 mm, 1510 mm
2010 mm

		LED Watt ¹	Luminous flux (lm) ²	Luminaire flux(lm) ²	Weight (kg) ³	Direction	LED Size	LED Finish	Control Mounting
 Down	1010 x 14 x 14 mm	10	1020	650	0.9	LYMD	10	BR	X
	2010 x 14 x 14 mm	15	1530	975	1.4	LYMD	15		
	2010 x 14 x 14 mm	20	2040	1300	1.8	LYMD	20		
 Up	1010 x 14 x 14 mm	10	1020	650	0.9	LYMU	10		
	1510 x 14 x 14 mm	15	1530	975	1.4	LYMU	15		
	2010 x 14 x 14 mm	20	2040	1300	1.8	LYMU	20		
 In	1010 x 14 x 14 mm	10	1020	650	0.9	LYMI	10		
	2010 x 14 x 14 mm	15	1530	975	1.4	LYMI	15		
	2010 x 14 x 14 mm	10	2040	1300	1.8	LYMI	20		
 Finish Satin brushed BR									
 LED Colour Warm White (Standard) - 3000°K CRI > 90+ (930) 930 Neutral White (Standard) - 4000°K CRI > 90+ (940) 940									
 Control NO DIMMER - default (00) 1-10V (40) Simple Remote (10) 0-10V (50) DALI / Push Dim (20) Casambi (60) DMX (30)									
 Mounting Suspended Ceiling or 24VDC wiring: Multiple point with integrated power cable (A) Canopy: Multi point with integrated power cable (C) X									
Cable length 2.5 m									

Full model number



LYMD - 10 - BR - 930 - 20 - C

1. Power rating and luminous output is for 3000°K CRI > 90
2. Rated values
3. Weight of luminaire only, excluding canopy , and power supply

- o Custom sizes available
- o Dialux LDT files available for download at oleant.com

O L E A N T

LYNAMURUS



Materials: Brass Extrusion, Polycarbonate diffuser
Designed by: Peter Danczkay
24 VDC 50,000 h L90/F50¹

Standard Sizes:
1010 mm, 1510 mm
2010 mm

		LED Watt ¹	Luminous flux (lm) ²	Luminaire flux(lm) ²	Weight (kg) ³	Direction	LED	Control	Mounting	
							Size	Finish		
Down	1010 x 14 x 14 mm	10	1020	650	0.9	LYMD	10			
	2010 x 14 x 14 mm	15	1530	975	1.4	LYMD	15			
	2010 x 14 x 14 mm	20	2040	1300	1.8	LYMD	20			
Up	1010 x 14 x 14 mm	10	1020	650	0.9	LYMU	10			
	1510 x 14 x 14 mm	15	1530	975	1.4	LYMU	15			
	2010 x 14 x 14 mm	20	2040	1300	1.8	LYMU	20			
In	1010 x 14 x 14 mm	10	1020	650	0.9	LYMI	10			
	2010 x 14 x 14 mm	15	1530	975	1.4	LYMI	15			
	2010 x 14 x 14 mm	10	2040	1300	1.8	LYMI	20			
Finish										
Satin brushed										
 BR										
LED Colour										
Warm White (Standard) - 3000°K CRI > 90+ --> 930 930										
Neutral White (Standard) - 4000°K CRI > 90+ --> 940 940										
Control										
NO DIMMER - default		(00)	1-10V	(40)						X
Simple Remote		(10)	0-10V	(50)						
DALI / Push Dim		(20)	Casambi	(60)						
DMX		(30)								
Mounting										
Foot length (only for direct surface mounting)										
6-10 cm										
*Power supply must be placed remotely										

Full model number



LYMD - 10 - BR - 930 - 20

1. Power rating and luminous output is for 3000°K CRI > 90
2. Rated values
3. Weight of luminaire only, excluding canopy , and power supply

- o Custom sizes available
- o Dialux LDT files available for download at oleant.com